

Hybrid Capacitor 2.3V 50F




FEATURES

Characteristics of EDLC and pseudo-capacitor
 Higher capacitance, 2 times of EDLC
 Semi-permanent, quick charge and discharge than batteries
 Suitable for long-term with low current backup applications
 UL and ISO/TS certificated, RoHS compliant
 Radial design with lead terminal type



DIMENSIONS



Dimensions in mm			
D +1.0 Max	L ± 1.5	d ± 0.1	P ± 0.5
Φ16.0	25.0	Φ0.8	7.5

This drawing is not to be scaled.

SPECIFICATIONS

Part Number	Rated Voltage, V_R (V)	Rated Capacitance (F)	AC ESR 1kHz (mΩ)	DC IR (mΩ)	Maximum Current (A)	Leakage Current (mA)	Stored Energy (J)	Dimension D x L (mm)	Weight (g)
VHC 2R3 506 QG	2.3	50.	60.00	160.00	1.5	0.100	132.3	16.0 x 25.0	8.5

* Maximum Current: 60 seconds discharge to $\frac{1}{2} \cdot V_R$

* Leakage Current: After 72hours at V_R and 25 °C

Item	Characteristics	Remarks
Rated Voltage(V_R)	2.3V	Cut-off voltage: 0.9V
Capacitance Tolerance	-10 ~ +30%	
Operating Temperature ($T_{min} \sim T_{max}$)	-25 ~ +60 °C	$ \Delta cap \leq 30\%$ of initial value at 25 °C $ \Delta ESR \leq 100\%$ of specified value at 25 °C After 1,000 hours application of V_R at T_{max}
Storage Temperature	-20 ~ +70 °C	
Cycle Life	100,000 cycles	$ \Delta cap \leq 30\%$ of initial value at 25 °C $ \Delta ESR \leq 100\%$ of specified value at 25 °C Cycles from V_R to $\frac{1}{2} \cdot V_R$ under constant current at 25 °C
Shelf Life	2 years	$ \Delta cap \leq 10\%$ of initial value at 25 °C $ \Delta ESR \leq 50\%$ of specified value at 25 °C Without electrical charge under T_{max}